



44279503 1 1227402

PATENT
GEN-001-97

5

DENTAL X-RAY APPARATUS

Technical Filed

The present invention is generally directed toward a dental x-ray apparatus. More particularly, the invention is directed toward an x-ray apparatus having a tube head formulated from a cast zinc material. Further, the invention also provides tube head components fabricated from a high molecular weight material, such as barium sulfite. More specifically, the tube head components are fabricated from a barium sulfite-charged plastic material. Further, the present invention is directed toward a DC powered x-ray dental apparatus.

15

BACKGROUND OF THE INVENTION

X-ray generators of small or moderate power for medical radiological application, normally use a fixed-anode x-ray tube (verses a rotating-anode x-ray tube as used when large power is required). In this case, the x-ray tube is usually contained in the same oil-filled housing as the high-voltage transformer and other components of the high-voltage circuit, and such an assembly is called a tubehead. During the last several years, x-ray generators commercially available for dental application (whether intraoral, panoramic, or other) have adopted this general design almost universally.

Inside the tubehead, the x-ray tube is supported by a mechanical part known as the tube holder, made out of a high-insulate and high electric tensile strength material, which performs essentially two functions:

REST AVAILABLE COPY

1) to securely and precisely hold the x-ray tube in position, in relation to the surrounding construction and in particular to the output windows and the external Beam-Limiting-Device; it ensures the accurate geometrical position of the x-ray source;

2) to generate high-voltage insulation between the x-ray tube (one or more of whose electrodes are at extremely high electrical potential) and the surrounding constructive metallic parts (in particular the housing) which are grounded.

In order to provide near-focus shielding against radiation from the x-ray tube (primary and extrafocal) in all directions except through a suitable output windows (thus greatly reducing the additional radiation shielding required for the housing as a whole), the tube holder is usually surrounded by a lead jacket, at least at the anode side and except for a small opening in correspondence with the wanted x-ray beam path.

The design and construction of this lead jacket may be critical, as any sharp or pointed detail (e.g., such as the thread of a screw) should be avoided because they imply singularities in the electric field and hence may cause high-voltage discharges.

Other structural components of the tube head, such as the housing or other such components, have typically been formulated from steel sheet metal, or cast aluminum alloys. Fabrication with welded steel sheet metal is relatively expensive, and quality might be difficult to control because it depends on the accuracy of the individual manufacturing process. Cast aluminum alloys requires special precautions to prevent oil leakage due to the fact that the material is often porous.

In both cases, but particularly when using aluminum, additional x-ray shielding is necessary. Lead plates or foil normally provide this shielding. Lead is an undesirable material to work with because of environmental and health issue concerns. In addition, lead shielding can either be placed inside the housing or outside the housing. In the case of inside shielding, the efficacy of the shielding cannot be visually inspected over time to

check for example, for positioning of the lead plates. Further, the lead and its associated components, such as lead protective paints, are potential contaminants to the dielectric-oil, and potentially can spoil the insulating performance of the oil. When placed outside the housing, the shielding may be mechanically damaged (lead is a soft material) by improper handling during production, installation or service. Further, the harmful lead is exposed. A need exists therefore for a dental x-ray apparatus having improved shielding and structural components.

DISCLOSURE OF THE INVENTION

10 It is therefore, an object of the present invention to provide a dental x-ray apparatus.

It is another object of the invention to provide a dental x-ray apparatus having improved structural and shielding components.

15 It is a further object of the invention to provide dental x-ray apparatus having a tube head formed from a cast zinc material.

It is an additional object of the invention to provide a dental x-ray apparatus having a tube head with structural and shielding components formed from a plastic impregnated with a high molecular weight material.

20 It is still a further object of the present invention to provide a dental x-ray apparatus wherein the structural components are formed from a plastic impregnated with barium sulfite.

In general, a dental x-ray apparatus comprises a housing, an x-ray tube, and structural components to support said x-ray tube. The housing is formulated from a cast of zinc material. The structural components, such as the tube carrier, are formulated from a plastic or resin material impregnated with a high molecular weight radiation absorber.

25

5 BRIEF DISCUSSION OF THE DRAWINGS

Fig. 2 is a close-up, perspective view of one portion of the tube head of Fig. 1.

PREFERRED EMBODIMENTS FOR CARRYING OUT THE INVENTION

4

Tube head housing 11 may be fabricated in any shape or design. An exemplary such tube head is shown by way of example on the accompanying drawings. Tube head 11 is preferably fabricated from a cast of zinc material. Zinc has a sufficiently high atomic number, and hence x-ray attenuation coefficient, as to provide enough shielding to secondary x-rays, i.e. against radiation leakage, without need for additional shielding such as those made from lead. Further, zinc lends itself well to casting, so it is suitable for such parts as a housing for tube head 11 with relatively thin and large walls. As is otherwise conventional, tube head 11 may be used to contain a dielectric oil. Further, zinc has sufficient mechanical properties to make it useful for structural components of the tube head. Zinc is also fairly inexpensive, is compact and has no inherent porosity. An additional advantage of zinc is that it is relatively lightweight.

As shown in Figs. 1 and 2, other components of the tube head 11 such as carrier 20 which is used to support an x-ray tube 21 is preferably fabricated from a plastic material impregnated with a radiation absorber. One preferred radiation absorber is barium sulfite. Barium sulfite is known for use as a contrast medium swallowed by a patient during gastro-intestinal radiography and as an additive to concrete for enhancing the radiation-shielding properties of masonry. It is generally considered to be not hazardous to health. Barium sulfite is also used as a charge added to certain types of products to enhance or change their mechanical properties. In the present invention, barium sulfite is used as an additive to the plastics of constructive parts inside the tube head, such as the tube holder or carrier 20, for the purpose of imparting radiation-shielding properties to otherwise radiation-transparent plastics. By making the x-ray tube holder out of a barium sulfite-charged plastic, the holder 20, which normally has a lead jacket, is free of such additional shielding. It is to be appreciated that lead, a generally hazardous and polluting material need not be used. Further, holder 20 is a one part

Although otherwise conventional, is it preferred that the present x-ray apparatus
5 be powered by a DC power supply.

10 the invention shall only the determined by the attached claims.